High Pressure Effects on the Superconductivity in Rare Earth Doped CaFe₂As₂

Dan Cargill^{1, 2}, Walter Uhoya², Krzysztof Gofryk³, Georgiy M. Tsoi², Yogesh K. Vohra², Athena S. Sefat³, and S. T. Weir⁴

¹Department of Physics, Hendrix College Conway, AR 17302, USA

²Department of Physics, University of Alabama at Birmingham (UAB), Birmingham, AL 35294,

USA

³Materials Science and Technology Division, Oak Ridge National Laboratory (ORNL), Oak Ridge, TN 37831, USA

⁴ Mail Stop L-041, Lawrence Livermore National Laboratory (LLNL), Livermore, CA 94550, USA

Abstract: High-pressure superconductivity in a rare-earth doped Ca_{0.86}Pr_{0.14}Fe₂As₂ single crystalline sample has been studied up to 12 GPa and temperatures down to 11 K using designer diamond anvil cell under a quasi-hydrostatic pressure medium. The electrical resistance measurements were complemented by high pressure and low temperature x-ray diffraction studies at a synchrotron source. The electrical resistance measurements show an intriguing observation of superconductivity under pressure, with T_c as high as ~51 K at 1.9 GPa, presenting the highest T_c reported in the intermetallic class of 1-2-2 iron-based superconductors. The resistive transition observed suggests a possible existence of two superconducting phases at low pressures of 0.5 GPa: one phase starting at T_{c1} ~48 K, and the other starting at T_{c2}~16 K. The two superconducting transitions show distinct variations with increasing pressure. High pressure low temperature structural studies indicate that the superconducting phase is a collapsed tetragonal ThCr₂Si₂-type (122) crystal structure. Our high pressure studies indicate that high T_c state attributed to non-bulk superconductivity in rare-earth doped 1-2-2 iron-based superconductors is stable under compression over a broad pressure range.

PACS: 62.50.-p, 74.62.Fj, 64.70.K-, PACS 61.50.Ks

Introduction

The interplay of high pressure and material chemistry has always played a pivotal role in the discovery and optimization of novel superconducting materials [1-3]. The discovery of superconductivity at 26 K in fluorine doped LaFeAsO_{1-x} F_x by Hosono et al in 2008 [4-5] has generated a lot of interest in related layered ferro-pnictides [6-10]. In the resulting researches, bulk superconductivity has been obtained in several layered ferro-pnictides under application of high pressure or chemical doping upon the suppression of spin-density-wave (SDW) state. However, the maximum T_c achieved to date in these compounds remains below 57 K achieved through electron doping in 1111 family [11] and 38 K achieved through hole doping in 122 family [12].

CaFe₂As₂ has the ThCr₂Si₂-type tetragonal (T) crystal structure at ambient conditions, and exhibits a tetragonal to orthorhombic structural transition and antiferromagnetic (AFM) ordering on cooling and a pressure-induced structural transition to a collapsed-tetragonal (CT) crystal structure at high pressures [1]. The structural and AFM transitions are suppressed under high pressures and superconductivity is induced with a T_C maximum reported under high pressure [1]. Another way to induce isostructural tetragonal structure collapse is through chemical pressure [13, 14]. Saha et al. reported that even 7.5 % substitution of Ca²⁺ with the rare-earth Pr³⁺ is enough to cause the electron doped compound to collapse upon cooling before 51 K with higher doping concentrations leading to higher temperature of structure collapse [14].

Unusually non-bulk superconductivity characterized by a mysterious small volume fraction which superconducts up to T_c onset = 42-49 K, much higher than the maximum $T_c \sim 38$ K in 122 family, has been realized in single crystalline rare earth doped $Ca_{1-x}Pr_xFe_2As_2$ [10, 13]. Qi et al. reported superconductivity with T_c up to 46 K for Pr doped $Ca_{87}Pr_{0.13}Fe_2As_2$ [15]. Lv et al. reported that all their $Ca_{1-x}Pr_xFe_2As_2$ samples doped between x=10.7% and 12.7% showed zero resistivity above 15 K with a superconducting onset as high as 49 K for x=12.7% doped sample [13]. Saha et al. reported an onset T_c reaching 47 K for 14% doping [14]. The T_c of 45-49 K reported in Pr-doped $Ca_{1-x}Pr_xFe_2As_2$ at ambient pressure is the highest among the 122 family of Fe-based superconductors [10, 13-15]. Recently, it has been suggested that the nature of the filamentary, anisotropic superconductivity in $Ca_{0.86}Pr_{0.14}Fe_2As_2$ could be interfacial as evidenced from the resistive and magnetic results [10, 13]. However, no high pressures studies have been reported on the transport properties of the RE-doped compounds hence it's still unclear how application high pressure could further tune their structural, magnetic and superconducting properties. Therefore, it would be interesting to study how pressure affects the

structural and interfacial superconducting properties of rare-earth doped CaFe₂As₂ compounds with optimal composition for high T_c . Pr doped Ca_{0.85}Pr_{0.13±2}Fe₂As₂ forms an ideal candidate for high pressure studies because it has the highest T_c (49 K) reported to date among the 122 Fe-based materials [10, 13].

In this report, a series of temperature- and pressure-dependent electrical resistance measurements, up to ~ 12.2 GPa and down to ~11 K, were undertaken to investigate the pressure evolution of superconductivity in rare earth doped single crystalline Ca_{0.86}Pr_{0.14}Fe₂As₂, using a designer-diamond anvil cell (DAC). We further carried out simultaneous pressure- and temperature-dependent x-ray diffraction studies on the sample down to 9 K to determine the crystalline structure of the superconducting phase of Ca_{0.86}Pr_{0.14}Fe₂As₂. Our studies show that the single crystalline Ca_{0.86}Pr_{0.14}Fe₂As₂ exhibit a unique successive double non-bulk superconducting transition that is absent from other 122-iron based superconductors. The higher transition temperature, T_{c1} is higher at lower pressures and decreases monotonically with pressure and could not be detected above 12 GPa for T >11 K. The lower transition temperature T_{c2} is fairly constant and disappears between P= 3.2 and 4 GPa. Onset of upper transition (T_{cl}) reaches a record high superconducting transition temperature of 51±1 K which exceed the highest T_c onset of bulk superconductivity ($T_c \sim 38$) [12] recorded for 122 materials either by chemical doping or high pressures. Our room temperature x-ray diffraction studies show that the collapsed tetragonal phase induced in Ca_{0.86}Pr_{0.14}Fe₂As₂ by cooling to 62 K is stabilized at room temperature by pressures as low as 0.5±0.2 GPa. Our low temperature studies shows that the crystal structure of the high pressure superconducting phase is ThCr₂Si₂ type collapsed tetragonal (CT) structure and the sample remains in the CT phase even at extreme pressures (7.5±0.2 GPa) and low temperatures (9 K) where the sample still displays signatures of non-bulk high-T_c superconductivity. This is the first report of high-pressure study of both structural and superconductivity in RE-doped Ca₁- $_{x}Re_{x}Fe_{2}As_{2}$

Experimental Details.

Large platelets of single-crystal samples of $Ca_{0.86}Pr_{0.14}Fe_2As_2$ were grown from FeAs flux, similar to that described in reference [16]. The crystals were characterized using energy dispersive x-ray spectroscopy (EDS), x-ray diffraction (XRD), temperature-dependent magnetization and electrical resistance measurements. High-pressure and low-temperature electrical resistance measurements were preformed on the single crystal $Ca_{0.86}Pr_{0.14}Fe_2As_2$ were performed using four-probe method in a sixtungsten microprobe designer DAC with 280µm size cullet as described earlier [17-18]. The eight tungsten microprobes are encapsulated in a homoepitaxial diamond film and are exposed only near the tip of the diamond to make contact with the sample. The sample was loaded into a 165 µm hole of a 225 µm thick spring-steel gasket that was first pre-indented to a ~100 µm thickness and mounted between a matched pair of the 280 µm cullet size designer diamond anvils and 300 µm cullet size matching diamond, ready for high-pressure and low temperature experiments. Two electrical leads pass constant 5μ A current through the sample and two additional leads measure voltage across the sample. Care was taken to electrically insulate the sample and the designer microprobes from the metallic gasket by using solid steatite as a pressure medium. In addition, the solid steatite pressure medium provides for a quasihydrostatic pressure measurement condition. Pressure was applied using a gas membrane to the designer DAC. For simultaneous temperature- and pressure-dependent x-ray diffraction experiments, the designer DAC was cooled down in a continuous helium flow-type-cryostat, and the pressure in the cell was measured *in situ* with the ruby fluorescence technique [18-19]. The synchrotron XRD experiments were performed at the high pressure beam-line 16-BM-D of HPCAT, at the Advanced Photon Source in Argonne National Laboratory. An angle dispersive technique with a MAR345 image-plate area detector was employed using a focused monochromatic beam with x-ray wavelength, $\lambda = 0.424600$ Å and sample to detector distance of 317.95 mm. The image plate XRD patterns were recorded with a focused x-ray beam of 5 µm by 7 µm (FWHM) on an 80 µm diameter sample mixed with ruby to serve as pressure marker. Experimental geometric constraints and the sample-to-image plate detector distance were calibrated using CeO₂ diffraction pattern and were held at the standard throughout the entirety of the experiment. The software package FIT2D [20] was used to integrate the collected MAR345 image plate diffraction patterns which were refined using GSAS [21] software package with EXPGUI interface [22] employing full-pattern Rietveld refinements and Le Bail fit techniques to extract structural parameters including atomic coordinates, bond angles, bond distances, lattice parameters, preferential orientation ratios.

Results and Discussions

Figure 1 shows the measured four probe electrical resistance of the Ca_{0.86}Pr_{0.14}Fe₂As₂ sample as a function of temperature at a fixed pressure of 0.5 ± 0.2 GPa. The figure also illustrates the criteria used for defining the onset of upper transition temperatures of superconductivity (T_{c1}) and lower transition temperature of superconductivity (T_{c2}) for the sample. The sample pressure was monitored continuously by an in situ ruby fluorescence system during cooling and warming cycles to detect any changes. The

pressure values reported are averages over the values recorded during the superconducting transition. The measured four probe electrical resistance shows two successive resistive transitions: an upper transition (T_{c1}) as shown by downturn in electrical resistance vs. temperature curve at the onset the upper transition. A second transition (T_{c2}) characterized by electrical resistance plateau followed by a sharper downturn occurs at lower temperatures relative to T_{c1} . The onset temperatures T_{c1} and T_{c2} is determined by the intersection of the two linear fits to the data above and below T_{c1} and T_{c2} , as illustrated for P = 0.5 GPa in figure 1. The onset of resistive transition for ~0.5±0.2 GPa occurs at $T_{c1} = 48$ K with lower transition occurring at $T_{c2} = 16$ K.

Figure 2 shows temperature dependence of the normalized electrical resistance of $Ca_{0.86}Pr_{0.14}Fe_2As_2$ at various pressures. The upper transition (T_{c1}), and lower one (T_{c2}) are all noticeable for lower pressures (P < 3.9 GPa). Above 3.9 GPa, onset T_{c1} gradually broadens and shifts to lower temperatures and eventually tend to vanish between 11.5 and 12.2 GPa for T > 11 K (figures 2, 3). The lower resistive transition T_{c2} curve as a function of pressure behaves qualitatively different; T_{c2} is fairly constant and is quickly suppressed below 11 K between 2.6 and 3.9 GPa, as compared to T_{c1} which persists over a wider pressure range. Further increase in pressure beyond 11.5 GPa leads to a gradual increase in the overall sample resistance at low temperatures. The two step transitions at low pressures and the broad width of upper resistive transition above pressures where lower resistive transition could not be individually detected suggests a high possibility for the existence of two superconducting phases.

Since the present electrical resistance measurements are restricted to temperatures above 11 K, it is possible that the onset of T_{c1} and T_{c2} transition may occur below 11 K for pressures greater than 11.5 GPa and 4 GPa, respectively. Note that electrical resistance do not become completely zero in the superconducting phases for this sample in all pressure range investigated as is the case for other 122 materials under pressure studied previously by our group under similar quasi-hydrostatic pressure conditions in designer diamonds. The T_{c1} of 48 K observed at ~0.5 GPa and the non-zero electrical resistance in the superconducting phase is consistent with recent reports on rare-earth CaFe₂As₂ at ambient pressure [10].

Figure 3 shows a clearer depiction of the evolution of the superconducting transition temperature with pressure. The onset temperature for the upper resistive transition T_{c1} increases fairly in a narrower pressure range reaching a maximum of ~51±1 K at only 1.9 GPa and then decreases gradually with further increasing pressure up to ~11 GPa. The measured is typically 33-36 K lower than T_{c1} , and T_{c2} decreases fairly linear as a function of pressure until a critical pressure of ~ 3.2 to 4 GPa above which it

could not be detected. The measured T_{c1} variation can be fitted by the following 3rd order polynomial equation over the entire pressure range, yielding T_{c1} of 45.1 K at ambient pressure. The maximum T_{c1} from the fit is at ~2.1 GPa and has a value of 51 K.

$$T_{cl}$$
 (in K) = 45.11±1.03 + 5.79±0.73P - 1.65±0.14P²+0.08±01P³, (P is pressure in GPa) (1)

The T_{c2} variation can be fitted by the following liner equation over the entire pressure range yielding 17.9 K at ambient pressure.

$$T_{C2}$$
 (in K) = 17.87±0.73 – 1.23±0.39P, (P is pressure in GPa) (2)

Our measured value of dT_{c1}/dP at ambient pressure (P \approx 0) is 5.79 K GPa⁻¹. This is higher in magnitude and different in sign as compared dT_{c2}/dP of -1.23 K GPa⁻¹ reported for second superconducting phase confined to the lower pressure region between 0 and 3.2 GPa.

Our results show that the T_{c1} dome for RE-doped CaFe₂As₂ is unusually broader extending over a wider pressure region as compared to typical pressure behavior of T_c for Fe-based superconductors which show a drastic decrease with increasing pressure over a narrow pressure region [1]. Additionally, measured T_{c1} values ranging from 45 to 51 K in the pressure range of 0 to 4 GPa are unusually higher for any known 122, 111, and 11 Fe-based superconductors under either chemical doping or pressure.

One possible explanation of the unique double superconducting resistive transitions, unusually high T_c values and the broader T_c vs. pressure dome is the existence of a low pressure minority phase in the Pr- doped Ca_{0.86}Pr_{0.14}Fe₂As₂, with tetragonal CaFe₂As₂ superconductor as one likely culprit. Given the layered nature of these materials; one can expect superconductivity to differently occur in the interface or intercalation places where doping is effective, forming numbers of superconducting sheets. These superconducting sheets consisting of low and high superconducting phases spread along the caxis direction only take up a small percentage of the whole crystal. The structural properties of the phases can evolve differently with pressure resulting to different T_c and magnetic properties evolution behavior. The low temperature resistive anomaly around 17 K at 0 GPa is suppressed by ~ 3.2 GPa and can be attributed to the small superconducting signal of the second phase. Previous studies show that the maximum T_c for undoped CaFe₂As₂ under pressure is about 11-13 K [1] which is less than 17 K. Our electrical resistance measurement when the sample was decompressing to 2.6 GPa suggest that T_{c1} is recovered at 47.5 K while the lower temperature phase could not be detected when pressure was released to 2.6 GPa. Additionally, Pr- doped $Ca_{0.86}Pr_{0.14}Fe_2As_2$ and $CaFe_2As_2$ are expected to have differing c-axis at ambient pressure and should be easily detected from diffraction studies. However, our x-ray diffraction study (see next sections) at ambient pressure and room temperature and at high pressures and low temperatures where the sample is superconducting does not show any evidence of secondary phases suggesting that a different possibility for the observed unusual trend from RE-doped $CaFe_2As_2$ exist.

Our optimal T_c values of 51 ± 1 K is consistent with that for the high temperature superconducting state for $Ca_{0.85}Pr_{0.13\pm2}Fe_2As_2$ with the maximum T_{c1} of 49 K [10,13]. Chu et al has attributed the non-bulk Josephson junction array nature of the 49 K superconducting transition together with its unusually high enhanced T_c to the probable long-sought-after interfacial mechanism for high temperature superconductivity proposed via exchange of excitons by Ginzburg in 1964 and Allender, Bray, and Bardeen in 1973 [23]. The origin for interfaces in a single crystalline sample has been determined by XRD to be misalignment of crystal grains which grows with doping along the FeAslayers in Pr doped $Ca_{0.85}Pr_{0.13\pm2}Fe_2As_2$. The group proposed further that the microstructure induced by nano-crystallographic strains in Pr doped $Ca_{0.85}Pr_{0.13\pm2}Fe_2As_2$ samples provide the proper nanomorphology conducive to interfacial superconductivity responsible for enhancement of T_c of the Prdoped sample to 49 K. [10, 23].

Figure 4 shows representative x-ray diffraction patterns of Ca_{0.86}Pr_{0.14}Fe₂As₂ sample obtained at various temperatures and pressures. Figure 4(a) shows Rietveld refinement of the x-ray diffraction pattern at ambient temperature and 0.5 GPa using the ThCr₂Si₂-type (*I*4/*mmm*) crystal symmetry with the unit cell atom positions given as: Ca/Pr atoms at the 2*a* position (0, 0, 0), Fe atoms at the 4*d* positions (0, 1/2, 1/4) and (1/2, 0, 1/4), and As atoms at the 4*e* positions (0, 0, *z*) and (0, 0, *-z*), and refined value of z given in Table 1. The crystallographic parameters including lattice parameters, unit cell volume, bond angles and distances obtained from the refinement of the XRD pattern at 0.5 GPa are summarized in Table 1. The diffraction lines are all identified and indexed and the difference between the observed x-ray diffraction pattern and Rietveld fit is satisfactory small suggesting a single phase tetragonal crystalline sample with ThCr₂Si₂ similar to earlier reports on parent 122 materials [1, 3, 6]. The As-As bond distance of 3.1059 Å obtained at 300 K and 0.5 GPa is nearly equal to critical value of ~ 3 which was determined to mark the onset of tetragonal to collapsed tetragonal (T-CT) structural transition in related 1-2-2 materials [14].

Figure 4 (b) shows the x-ray diffraction pattern of the superconducting Ca_{0.86}Pr_{0.14}Fe₂As₂ at 9 K and 7.5 GPa where the sample is expected to be superconducting with a T_{c2} onset of ~28 K as depicted in figure 3. The low temperature XRD pattern is similar to the room temperature pattern suggesting that the symmetry is also tetragonal. The Rietveld refinements of the x-ray diffraction pattern (figure. 1 (b) confirmed a ThCr₂Si₂ type tetragonal crystal structure with lattice parameters a = 3.9971 Å, c = 10.1491Å, volume V=162.1463 Å³, an axial ratio (c/a) =2.5391, atomic parameter z = 0.361356, As-Fe-As bond angle α =104.023(9) degrees and As-As bond distance of 2.8142(10) Å. Comparison the values obtained at 9 K, 7.5 GPa with the low pressure and room temperature values show an increase in a-lattice parameter while *c*-lattice parameter is strongly reduced suggesting a formation of the isostructural tetragonal collapsed phase. The As-As interlayer separation was determined to be the key parameter controlling the isostructural tetragonal structure collapse in 122 materials: CaFe₂As₂ crystal collapse once the interlayer As-As distance reaches a critical value of ~ 3 Å where As p-orbitals overlap upon application high pressure or rare-earth doping [14]. The measured As-As distance for our sample at 9 K and 7.5 GPa is 2.8142(10) Å confirming that the high- T_c superconducting phase remains in the collapsed structure phase at higher pressures. Full structural refinement data for Ca_{0.86}Pr_{0.14}Fe₂As₂ at 9 K and 7.5 GPa in the stabilized collapsed phase are tabulated in Table I. It is believed that T_C values are maximum when the corrugated FeAs layers exhibit coordination close to the ideal tetrahedral configuration ($\alpha =$ 109.9). Applied pressure drives the structure away from this ideal tetrahedral coordination by 3.4 % at 0.5 GPa where T_c is 48 K and by 5.35% at 7.5 GPa in the CT phase.

Conclusions

In summary, pressure and temperature-dependent electrical resistance measurements are reported on $Ca_{0.86}Pr_{0.14}Fe_2As_2$ using a designer DAC to 12.2 GPa and down to 11 K. The resistance measurements show an evidence of a pressure-enhanced superconductivity with a remarkable maximum T_{c1} of ~51 K at only 1.9 GPa. The onset of superconducting transition temperature decreases with increasing pressure and disappears for pressures above ~12 GPa above 11 K. The complementary x-ray diffraction studies conducted under high pressure and low temperature conditions suggest that that the crystal structure of the superconducting phase of the rare rare-earth doped $Ca_{0.86}Pr_{0.14}Fe_2As_2$ is of the collapsed tetragonal Th Cr_2Si_2 -type. Our results show that for certain levels of rare earth doping into 122 compounds, pressure may be a viable means of further optimizing T_c and transition temperatures as high as 51 K or

more may be obtainable. Our high pressure studies indicate that the high- T_c superconductivity in REdoped 1-2-2 iron-based superconductors is stable over a broad pressure range.

Acknowledgment

Dan Cargill acknowledges support from the National Aeronautics and Space Administration (NASA)-Alabama Space Grant Consortium, National Science Foundation (NSF) Research Experiences for Undergraduates (REU)-site under grant no. NSF-DMR-1058974 awarded to UAB. Walter Uhoya acknowledges support from the Carnegie/Department of Energy (DOE) Alliance Center

(CDAC) under grant no. DE-NA0002006. The work at ORNL was supported by the Department of Energy, Basic Energy Sciences, Materials Sciences and Engineering Division. Portions of this work were performed in a synchrotron facility at HPCAT (Sector 16), Advanced Photon Source (APS), Argonne National Laboratory. We are grateful to J. E. Mitchell for growing the single crystal of $Ca_{0.86}Pr_{0.14}Fe_2As_2$.

References

- [1] A.S. Sefat, Reports on Progress in Physics, 74 (2011) 124502.
- [2] S. James, H. Narelle, F. Neda, Journal of Physics: Conference Series, 449 (2013) 012021.
- [3] C.W. Chu, B. Lorenz, Physica C: 469 (2009) 385-395.
- [4] Y. Kamihara, T. Watanabe, M. Hirano, H. Hosono, J Am Chem Soc, 130 (2008) 3296-3297.
- [5] H. Takahashi, K. Igawa, K. Arii, Y. Kamihara, M. Hirano, H. Hosono, Nature, 453 (2008) 376-378.
- [6] D.C. Johnston, Advances in Physics, **59** (2010) 803-1061.
- [7] J. Paglione, R.L. Greene, Nat Phys, 6 (2010) 645-658.
- [8] M.V. Sadovskii, Physics-Uspekhi, **51** (2008) 1201.
- [9] G.R. Stewart, Reviews of Modern Physics, 83 (2011) 1589-1652.
- [10] C.W. Chu, Physica C: Superconductivity, 482 (2012) 33-44.
- [11] Z. Wei, H.o. Li, W. Hong, Z. Lv, H. Wu, X. Guo, K. Ruan, J Supercond Nov Magn, 21 (2008) 213-215.
- [12] M. Rotter, M. Tegel, D. Johrendt, Phys Rev Lett, **101** (2008) 107006.
- [13] B. Lv, L. Deng, M. Gooch, F. Wei, Y. Sun, J.K. Meen, Y.-Y. Xue, B. Lorenz, C.-W. Chu, Proceedings of the National Academy of Sciences, **108** (2011) 15705-15709.
- [14] S.R. Saha, N.P. Butch, T. Drye, J. Magill, S. Ziemak, K. Kirshenbaum, P.Y. Zavalij, J.W. Lynn, J. Paglione, Physical Review B, 85 (2012) 024525.
- [15] Y. Qi, Z. Gao, L. Wang, D. Wang, X. Zhang, C. Yao, C. Wang, C. Wang, Y. Ma, Superconductor Science and Technology, **25** (2012) 045007.
- [16] A.S. Sefat, K. Marty, A.D. Christianson, B. Saparov, M.A. McGuire, M.D. Lumsden, W. Tian, B.C. Sales, Physical Review B, 85 (2012) 024503.
- [17] S.T. Weir, J. Akella, C. Aracne-Ruddle, Y.K. Vohra, S.A. Catledge, Applied Physics Letters, **77** (2000) 3400-3402.
- [18] G. Tsoi, A.K. Stemshorn, Y.K. Vohra, P.M. Wu, F.C. Hsu, Y.L. Huang, M.K. Wu, K.W. Yeh, S.T. Weir, J Phys Condens Matter, 21 (2009) 232201.
- [19] J. Yen, M. Nicol, Journal of Applied Physics, 72 (1992) 5535-5538.
- [20] A.P. Hammersley, Report No. EXP/AH/95-01, (1995).
- [21] A.C. Larson, R.B.V. Dreele, Los Alamos National Laboratory Report LAUR, 86-748 (2004).
- [22] B. Toby, Journal of Applied Crystallography, **34** (2001) 210-213.
- [23] D. Allender, J. Bray, J. Bardeen, Physical Review B, 7 (1973) 1020-1029.

Figure Captions

Figure 1. (Color online). Temperature dependence of the electrical resistance of rare earth doped $Ca_{0.86}Pr_{0.14}Fe_2As_2$ at 0.5 GPa. Steatite was used as pressure medium and pressure was calibrated using ruby fluorescence.

Figure 2. (Color online). Temperature dependence of the electrical resistance of rare earth doped $Ca_{0.86}Pr_{0.14}Fe_2As_2$ at various applied pressures. Steatite was used as pressure medium, and pressure was calibrated using ruby fluorescence.

Figure 3. (Color online). Measured superconducting transition temperature for $Ca_{0.86}Pr_{0.14}Fe_2As_2$ as a function of pressure, by onset temperature criterion shown as T_{c1} and T_{c2} . The solid curves are third order polynomial fit to T_{c1} data and liner fit to T_{c2} data, (see text for detail).

Figure 4. (Color online) Rietveld refinement of powder x-ray diffraction patterns of $Ca_{0.86}Pr_{0.14}Fe_2As_2$ in the ThCr₂Si₂ (I4/mmm) crystal phase at (a) ambient temperature and 0.5 ± 0.2 GPa, and at (b) 9 K and 7.5±0.3 GPa. The lowermost solid line (magenta) in (a) and (b) are the difference profile curves between the observed (solid red symbols) and calculated (green line) profiles. The hkl values for peaks corresponding to the tetragonal *I*4/*mmm* phase are marked by the black lines. The crystallographic parameters obtained from GSAS refinement are summarized in Table 1.



Figure 1



Figure 2



Figure 3



Figure 4 (a)



Figure 4 (b)

TABLE I. Crystallographic data for $Ca_{0.86}Pr_{0.14}Fe_2As_2$ crystals as determined from GSAS refinement of synchrotron x-ray diffraction for selected pressures and temperatures at which the sample adopt the collapsed tetragonal ThCr₂Si₂ (122) crystal structure. Atomic positions for space group I4/*mmm* are: Ca/Pr at 2*a* position (0, 0, 0); Fe at 4*d* positions (0, 1/2, 1/4) and (1/2, 0, 1/4); and As at 4*e* positions (0, 0, z) and (0, 0, -z). The measurements were carried out using a focused x-ray monochromatic beam of wavelength 0.4246 Å. Sample shows preferred orientation along (001) with a GSAS refinement March-Dollase Preferential Orientation ratio of 2.45539 at (9 K, 7.5 GPa) and 2.382975 at (0.5 GPa, 300 K).

Temperature	300 K	9 K
Pressure	0.5 GPa	7.5 GPa
Space Group(phase)	I4/mmm	I4/mmm
Lattice parameter, $a=b$ (Å)	3.936922(1)	3.99705(63)
Lattice parameter, c (Å)	11.106790(2)	10.14911(652)
Unit cell volume, $V(\text{\AA}^3)$	172.1481	162.1463
Atomic parameter, (z,-z)	0.360178, 0.639822	0.361356, 0.638644
Ca/Pr U-iso	0.04156	0.04146
Fe U-iso	0.11294	0.07555
As U-iso	0.07759	0.08304
GSAS wRp	0.1049	0.1250
GSAS Rp	0.0650	0.0807
Reduced Chi ^2	0.2630	0.5993
Bond Angles (deg)		
As-Fe-AS (a)	106.1859(11)	104.023(14)
As-Fe-AS (β)	116.2644(15)	121.024(32)
Fe-As-Fe	73.8148(8)	75.977(14)
Bond lengths (Å)		
As-As	3.1059(10)	2.8142(18)
Fe-As	2.3178 (9)	2.2959(4)
Fe-Fe	2.78382(33)	2.8263(4)